

DESIGN FUNCTION PERFORMANCE



Oil Storage Tanks Product Guide

Bunded and fire protected oil storage tanks available from 1,000 to 15,000 litres









Built on Trust

The Tuffa range of oil storage tanks is well-regarded in the industry and has been trusted by businesses, homes, and farms for their heating needs for more than 30 years. Tanks are available from 1,000 to 100,000 litres offering more than 30 sizes and shapes to suit all installations.



Why Tuffa?

- We are a British manufacturer with more than 30 years design and manufacturing experience.
- We don't compromise on quality.
- We design solutions in both plastic and steel.
- We offer competitive pricing.



The Benefits

With Tuffa, you will benefit from the following:

- Service and aftersales care direct from the manufacturer.
- Minimum 20-year design life and 10-year warranty on all bunded tanks, when registered.
- Tanks compatible with kerosene, gas oil and E-fuels such as HVO.
- Premium materials and equipment at competitive rates.
- Loyalty to our dealers.
- Industry approved tanks that are CE marked and fully compliant with current regulations and safety standards.











2

Models and Specifications

Bunded Oil Tanks / Plastic	
1350SLB Capacity Length Width Height Weight 1.350 litres 2,680mm 870mm 1.665mm 170kg	Capacity Diameter Height Weight 6,000 litres 2,550mm 2,585mm 360kg Cabinet: Height Width Depth Weight 2,000mm 1,200mm 600mm 50kg
Labore Height Weight 1,400 litres 1,585mm 1,750mm 120kg	IDOOOVB Capacity Diameter Height Weight 10,000 litres 2,890mm 2,590mm 430kg Cabinet: Height Width Depth Weight 2,000mm 1,200mm 600mm 50kg
2500HB Capacity Length Width Height Weight 2,500 litres 2,840mm 1520mm 1,630mm 260kg	List Diameter Height Weight 15,000 litres 2,890mm 3,500mm 630kg Height Width Depth Weight Cabinet: 400mm 1,200mm 600mm 50kg
S500VB Capacity Diameter Height Weight 3,500 litres 2,013mm 2,520mm 280kg Height Width Depth Weight 2,000mm 1,200mm 600mm 50kg	Faster Installs Our steel tank models have
Bunded Oil Tanks / Steel	been designed to accommodate pre-fabricated concrete bases, for faster installs and cheaper costs.
Stoomm × W Stoomm × W Stoomm × W Stoomm × W Stoomm × W Stoomm × W Id500SB Stoomm × W Capacity Length Width Id500Itrues Id600mm Id500Itrues Id600mm Id500Itrues Id600mm Id600Itrues Id600mm Id600mm	2300SB Capacity Length Width Height Weight 2,325 litres 1,800mm 1,200mm 1,680mm 450kg
tuffa	Yes Y

Models and Specifications

Specifications – Bunded Oil Tanks

	Small Plastic - Standard	Small Plastic - Watchman	Large Plastic - No Cabinet	Large Plastic - Cabinet	Small Steel - Standard	Small Steel - Bare Tank
Feature	1350-2500L	1350-2500L	3500-15000L	3500-15000L	1000-2300L	1000-2300L
2" BSP fill point	1	1	1	1	1	
Overfill prevention valve	 ✓ 	1	1	1	 Image: A set of the set of the	
Vent	1	1	1	1	<i>✓</i>	
Manual float level gauge	 ✓ 	1			 Image: A set of the set of the	
Watchman Sonic		1	1	1	002-T & 004-T models	
% Hydrostatic gauge				1		
Battery bund and overfill alarm				1		
Lockable flip lid	1	1				
600mm screwlid			1	1		
2" spare socket					 Image: A set of the set of the	√ x2
1.5" spare socket						1
1" bottom outlet	 ✓ 	1	 Image: A second s	1	 Image: A set of the set of the	1
Top outlet	003-T models only	004-T models only	003-T models only	004-T models only	003-T & 004-T models	
Fittings kit	001-T models only	002-T models only			001-T & 002-T models	
Cabinet				1		
Channel runners					 Image: A second s	1
Central lifting eye					1	1
Touch up paint					 Image: A set of the set of the	
Codes	1350SLB-001-T 1400VB-001-T 2500HB-001-T 1350SLB-003-T 1400VB-003-T 2500HB-003-T	1350SLB-002-T 1400VB-002-T 2500HB-002-T 1350SLB-004-T 1400VB-004-T 2500HB-004-T	3500VB-001-T 6000VB-001-T 10000VB-001-T 15000VB-001-T 3500VB-003-T 6000VB-003-T 15000VB-003-T 15000VB-003-T	3500VB-002-T 6000VB-002-T 10000VB-002-T 15000VB-002-T 3500VB-004-T 6000VB-004-T 10000VB-004-T 15000VB-004-T	1000SB-001-T 1650SB-001-T 2300SB-001-T 1000SB-002-T 1650SB-002-T 2300SB-002-T 1000SB-003-T 1650SB-003-T	1000SB-005-T 1650SB-005-T 2300SB-005-T



4





bespoke **tanks**

A bespoke tank fabrication allows you to build a tank to your specification

custom tanks 🔿



Models and	l Specif	ication	S					
Fire Protecte	d Oil Tai	nks / Plc	astic				FIRE	
1350S Capacity	Juin	LINE	Weight		2500 Capacity	HBFP	/idth Height	Weight
1,150 litres	2,680mm 870	mm 1,665mm ⁻	195kg 238kg		2,440 litre	es 2,840mm 1,4	520mm 1,630mr	n 290kg 337kg
	Diameter He	ight Weig 30min 6 50mm 140kg 1	ht omin 71kg					
Fire Protecte	d Oil Ta	nks / Ste	eel			limlin anks	ie >[<
1000S	Length Widt		Weight ^{80min 60min} 40kg 370kg				ace is rest er moveme	
	00mm × 🔀	600	Omm x x2					
	Length Widt 1,800mm 900m		Weight ^{60min 60min} 10kg 455kg		2300 Capacity 2,325 litres	Length W	idth Height	Weight 30min 60min n 815kg 870kg
ROAD 8	00mm × x6 00mm × x6	600	Omm x x3	A IMPROJU		900mm x x6 600mm		00mm x x3
Specification	ns — Fire	Protect	ed Oil To	anks				
	Plastic FP BO - 30min	Steel FP BO - 30min	Plastic FP TO - 30min	Steel FP TO - 30min	Plastic FP BO - 60min	Steel FP BO - 60min	Plastic FP TO - 60min	Steel FP TO - 60min
Feature	1350-2500L	1000-2300L	1350-2500L	1000-2300L	1350-2500L	1000-2300L	1350-2500L	1000-2300L
Fire Protection	1	1	1	 ✓ 	 ✓ 	 Image: A set of the set of the	1	1
2" BSP fill point	1	1	1	1	1	1	1	1
Overfill prevention valve	1	✓	1	✓	1	✓	1	1
Vent Manual flagst lawal agence					1		1	
Manual float level gauge Watchman Sonic					<i>J</i>	<i>J</i>		
Lockable flip lid		V		· ·				•
1" bottom outlet	1	1			1	1	•	
				1			(
Top outlet				· ·			1	1
Fittings kit		✓ ✓			1	1	<i></i>	
Fittings kit Central lifting eye	1	1			 Image: A second s	1		
Fittings kit Central lifting eye Channel runners	✓ 				✓ 			
Fittings kit Central lifting eye	1350SLBFP-001-T	1	1350SI BEP-002-T		1350SLBFP-003-T	1	1350SLBFP-004-T	



What is FirePro[®]?

FirePro[®] is a tier-one bunded oil tank that's integrally fitted with a unique, patented fire jacket providing 30 or 60-minute fire protection.

Our unique product provides compliant installation as close as 300mm from the walls or boundaries and can even be installed inside domestic outbuildings.

FirePro® is a perfect choice when:

- Replacing an oil tank in a location which is no longer compliant.
- Space is limited, and you're struggling to comply with Building Regulations.
- You want to locate your oil tank discreetly to preserve the look and feel of your outside areas.
- You want to avoid lengthy installations, building works and unsightly fireboards.
- You want to install a tank safely inside a domestic outbuilding (e.g. garage) or under a lean-to.







Who can install and certify a fire rated oil tank?

a. Competent Persons

i. Technicians within Competent Persons Schemes such as the Association of Plumbing and Heating Contractos (APHC) can fit and certifiy the oil tank without prior approval from building control.

b. End User/Installer

i. Tuffa have partnered with Approved Inspectors Stroma and developed a simple 4-step process that Stroma can self-certify, often remotely.



6

- **Step 1:** Complete the Stroma application form and send to them directly. This must be submitted a minimum of 7 days before works commence on site.
- **Step 2:** Provide any images or additional information as required.
- **Step 3:** Once the tank is installed, email the final installation photos and Compliance Declaration Form to Stroma.
- **Step 4:** Pay the £150.00 plus VAT sign-off fee and wait for the certification direct from Stroma.

